





## BULK, FORMING (not available for taping)


FORMING STYLE	FORMING TYPE NAME	FORMING DIMENSION (mm)				WEIGHT g/100pcs	Q'TY/BAG (pcs)	Q'TY/BOX (pcs)
		P ± 1	H <sub>3</sub> ± 1 or H <sub>5</sub>	H <sub>4</sub> ± 1 or H <sub>6</sub>	d			
<b>L Forming</b> 	CW1/2CL10A	10.0	5.3	4.5 ± 0.5	0.6	24	100	2000
	CW1(P/H)CL12.5A	12.5	6.5	4.0 ± 0.5	0.8	56	100	2000
	CW1(P/H)CL15A	15.0	5.3	4.5 ± 0.5	0.8	56	100	2000
	CW2(P/H)CL15A	15.0	7.0	4.5 ± 0.5	0.8	84	100	2000
	CW2(P/H)CL20A	20.0	8.0	4.5 ± 0.5	0.8	84	100	2000
	CW3(P/H)CL20A	20.0	8.0	4.0 ± 0.5	0.8	160	100	1000
	CW3(P/H)CL25A	25.0	7.0	4.5 ± 0.5	0.8	160	100	1000
	CW5CL30A	30.0	8.5	4.5 ± 0.5	0.8	524	50	500
	CW5CL35A	35.0	5.5	4.5 ± 0.5	0.8	524	50	500
	MO(X)1/2CL12.5A	12.5	6.5	4.0	0.8	52	100	2000
	MO(X)1/2CL15A	15.0	5.3	4.0	0.8	52	100	2000
	MO(X)1CL15A	15.0	7.0	4.0	0.8	69	100	2000
	MO(X)1CL20A	20.0	4.8	4.0	0.8	69	100	2000
	MO(X)2CL20A	20.0	8.0	4.0	0.8	142	100	1000
	MO(X)2CL25A	25.0	7.0	4.0	0.8	142	100	1000
	MO(X)3CL30A	30.0	8.5	4.0	0.8	460	50	500
	MO(X)3CL35A	35.0	5.5	4.0	0.8	460	50	500
	MOS(X)1/2CL10A	10.0	5.3	4.0	0.6	23	100	2000
	MOS(X)1CL12.5A	12.5	7.0	4.0	0.8	31	100	2000
	MOS(X)1CL15A	15.0	6.5	4.0	0.8	31	100	2000
	MOS(X)2CL15A	15.0	7.0	4.0	0.8	71	100	2000
	MOS(X)2CL20A	20.0	9.0	4.0	0.8	71	100	2000
	MOS(X)3CL20A	20.0	8.0	4.0	0.8	146	100	1000
	MOS(X)3CL25A	25.0	7.0	4.0	0.8	146	100	1000
	MOS(X)5CL30A	30.0	8.5	4.0	0.8	524	50	500
	MOS(X)5CL35A	35.0	5.5	4.0	0.8	524	50	500
	SPR(X)1/2CL10A	10.0	5.3	4.0	0.6	23	100	2000
	SPR(X)1CL12.5A	12.5	6.5	4.0	0.8	54	100	2000
	SPR(X)1CL15A	15.0	5.3	4.0	0.8	54	100	2000
	SPR(X)2CL15A	15.0	7.0	4.0	0.8	71	100	2000
	SPR(X)2CL20A	20.0	9.0	4.0	0.8	71	100	2000
	SPR(X)3CL20A	20.0	8.0	4.0	0.8	141	100	1000
	SPR(X)3CL25A	25.0	7.0	4.0	0.8	141	100	1000
	SPR(X)5CL30A	30.0	8.5	4.0	0.8	456	50	500
	SPR(X)5CL35A	35.0	5.5	4.0	0.8	456	50	500
	RCR50ENCL15A	15.0	5.3	4.5	0.7	34	100	2000
	RCR50+CL15A	15.0	5.3	4.5	0.7	34	100	2000
	RCR60CL15A	15.0	5.3	4.5	0.7	34	100	2000
	RCR75CL15A	15.0	7.0	4.5	0.8	69	100	2000
	RCR100CL25A	25.0	7.0	4.0	0.8	142	100	1000
	RK1/4□CL10A	10.0	5.3	4.5	0.6	23	100	1000
	RK1□CL20A	20.0	8.8	4.5	0.8	146	100	1000
	CFP1/4CL10A	10.0	6.5	4.5	0.65	23	100	1000
	CFPB1/2CL12.5A	12.5	6.5	4.5	0.65	44	100	1000
	RF25CL10A	10.0	5.35	5.0	0.6	23	100	2000
RF50CL12.5A	12.5	6.0	5.2	0.6	29	100	2000	
RF50CL15A	15.0	6.0	5.3	0.6	29	100	2000	
RF1CL12.5A	12.5	6.5	4.8	0.8	46	100	2000	
RF1CL15A	15.0	5.3	4.5	0.8	46	100	2000	
RF1CL20A	20.0	5.3	4.5	0.8	46	100	2000	
RF2CL20A	20.0	8.0	5.0	0.8	141	100	1000	
RF2CL25A	25.0	7.0	4.5	0.8	141	100	1000	
<b>U Forming</b> 	MFS1/4□□CU	—	5.5 Max.	15.0 ± 1.0	0.45	14	200	2000
	CFS1/4CU	—	5.5 Max.	15.0 ± 1.0	0.45	12	200	2000
<b>U Forming</b> 	MF1/4□□CU	—	9.5 Max.	30.0 ± 3.0	0.6	23	100	2000
	MFP1/4□□CU	—	9.5 Max.	30.0 ± 3.0	0.6	23	100	2000
	RK1/4□□CU	—	9.5 Max.	30.0 ± 3.0	0.6	23	100	1000
	RK1/4□□CUC-5	—	9.5 Max.	5.0 ± 1.0	0.6	23	100	1000
	CF1/4CUC	—	10.0 Max.	10.0 ± 1.0	0.6	23	100	1000
	CFS1/2CU	—	9.5 Max.	30.0 ± 3.0	0.6	44	100	1000
<b>U Forming</b> 	LT1/4CU	—	9.5 Max.	30.0 ± 3.0	0.6	23	100	2000
	MO(X)1/2CU	—	19.5 ± 3.0	15.0 Min.	0.7	49	100	1000
	MO(X)1CU	—	24.0 ± 3.0	15.0 Min.	0.8	69	100	1000
	MO(X)2CU	—	25.0 ± 3.0	15.0 Min.	0.8	71	100	1000
	MOS(X)1CU	—	19.5 ± 3.0	15.0 Min.	0.8	23	100	1000
	MOS(X)2CU	—	22.0 ± 3.0	15.0 Min.	0.8	71	100	1000
	MOS(X)3CU	—	25.0 ± 3.0	15.0 Min.	0.8	146	100	1000
	SPR(X)1CU	—	19.5 ± 3.0	15.0 Min.	0.8	54	100	1000
	SPR(X)2CU	—	22.0 ± 3.0	15.0 Min.	0.8	93	100	1000
SPR(X)3CU	—	25.0 ± 3.0	15.0 Min.	0.8	141	100	1000	

Contact our sales representatives before you use our products for applications including automobiles, medical equipment and aerospace equipment. Malfunction or failure of the products in such applications may cause loss of human life or serious damage.

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order or use.

T.C.R. symbol is to be entered in the □

## BULK, FORMING (not available for taping)

FORMING STYLE	FORMING TYPE NAME	FORMING DIMENSION (mm)					WEIGHT g/100pcs	Q'TY/BAG (pcs)	Q'TY/BOX (pcs)
		P ± 1	H <sub>1</sub>	H <sub>2</sub>	e MAX.	d			
M Forming 	MFS1/4□□CM5F	5.0	-	5.0 ± 1.0	2.0	0.45	14	200	2000
	MFS1/4□□CM5R	5.0	10.0 ± 1.0	-	2.0	0.45	14	200	2000
	MFS1/4□□CM5W	5.0	-	15.0	2.0	0.45	14	200	2000
	MF1/4□□CM10F	10.0	-	5.0 ± 1.0	2.0	0.6	23	100	2000
	MF1/4□□CM12.5R	12.5	10.0 ± 1.0	-	2.0	0.6	23	100	2000
	MF1/2□□CM12.5R	12.5	10.0 ± 1.0	-	2.0	0.6	41	100	2000
	MF1/2□□CM15R	15.0	10.0 ± 1.0	-	2.0	0.6	41	100	2000
	MFP1/4□□CM10F	10.0	-	5.0 ± 1.0	1.7	0.6	24	100	2000
	MFP1/4□□CM12.5R	12.5	10.0 ± 1.0	-	1.7	0.6	24	100	2000
	MFP1/2□□CM12.5R	12.5	10.0 ± 1.0	-	2.0	0.7	41	100	2000
	MFP1/2□□CM15R	15.0	10.0 ± 1.0	-	2.0	0.7	41	100	2000
	SNF2CCM5F	5.0	-	5.0 ± 1.0	1.5	0.45	14	200	2000
	SNF2ECM10F	10.0	-	5.0 ± 1.0	1.7	0.6	24	100	2000
	SNF2ECM12.5R	12.5	10.0 ± 1.0	-	1.7	0.6	24	100	2000
	SNF2HCM12.5K	12.5	7.0 ± 1.0	-	2.0	0.7	41	100	2000
	SNF2HCM15K	15.0	7.0 ± 1.0	-	2.0	0.7	41	100	2000
	RCR16CM5F	5.0	-	5.0 ± 1.0	2.0	0.45	14	200	2000
	RCR25CM10F	10.0	-	5.0 ± 1.0	2.0	0.6	23	200	2000
	RCR50CM15F	15.0	-	5.0 ± 1.0	2.0	0.7	40	100	2000
	RCR50+CM15F	15.0	-	5.0 ± 1.0	2.0	0.7	40	100	2000
	RCR60CM15F	15.0	-	5.0 ± 1.0	2.0	0.7	40	100	2000
	RCR100CM20E	20.0	-	4.6 ± 1.0	2.0	0.8	120	100	1000
	RK1/4□□CM10F	10.0	-	5.0 ± 1.0	1.7	0.6	21	100	1000
	RK1/4□□CM10R	10.0	-	10.0 ± 1.0	1.7	0.6	21	100	1000
	RK1/4□□CM12.5R	12.5	-	10.0 ± 1.0	1.7	0.6	23	100	1000
	RK1/2□□CM15F	15.0	-	5.0 ± 1.0	2.0	0.6	40	100	1000
	RK1/2□□CM12.5F	12.5	-	5.0 ± 1.0	2.0	0.6	37	100	1000
	RK1/2□□CM15R	15.0	-	10.0 ± 1.0	2.0	0.6	37	100	1000
	CFS1/4CM5F	5.0	5.9 ± 1.0	5.0 ± 1.0	1.5	0.45	12	200	2000
	CF1/4CM10H	10.0	6.0 ± 1.0	4.8 ± 1.0	1.7	0.6	23	100	1000
	CF1/4CM12.5H	12.5	6.0 ± 1.0	4.8 ± 1.0	1.7	0.6	23	100	1000
	CFB1/2CM12.5K	12.5	7.0 ± 1.0	5.0 ± 1.0	1.7	0.7	44	100	1000
	CFS1/2CM10H	10.0	6.0 ± 1.0	4.8 ± 1.0	1.7	0.6	26	100	1000
	CFPS1/4CM5F	5.0	5.9 ± 1.0	5.0 ± 1.0	1.5	0.45	12	200	2000
	CFP1/4CM10H	10.0	6.0 ± 1.0	4.8 ± 1.0	1.7	0.6	23	100	1000
	CFPB1/2 CM12.5K	12.5	7.0 ± 1.0	5.0 ± 1.0	2.0	0.7	44	100	1000
	LT1/6CM5F	5.0	-	5.0 ± 1.0	2.0	0.45	14	200	2000
	LT1/6CM5R	5.0	10.0 ± 1.0	-	2.0	0.45	14	200	2000
	LT1/6CM5W	5.0	-	15.0	2.0	0.45	14	200	2000
	LT1/4CM10F	10.0	-	5.0 ± 1.0	2.0	0.6	23	100	2000
	LT1/4CM10R	10.0	10.0 ± 1.0	-	2.0	0.6	23	100	2000
	LT1/4CM12.5R	12.5	10.0 ± 1.0	-	2.0	0.6	23	100	2000
	J1/6ZCM7.5H	7.5	-	5.0 <sup>+2.0</sup>	1.5	0.5	5	100	1000
	J1/4ZCM10H	10.0	-	5.0 <sup>+2.0</sup>	1.5	0.6	9	100	1000
	RF16CM5F	5.0	-	5.0 ± 1.0	2.0	0.45	12	200	2000
RF25CM10X	10.0	16.0 ± 1.0	14.8 ± 1.0	1.5	0.6	23	100	1000	
RF50CM12.5E	12.5	-	4.5 ± 1.0	1.5	0.6	29	100	1000	
RF1CM15F	15.0	-	5.0 ± 1.0	1.5	0.8	46	100	1000	
MO(X)1/2CM15F	15.0	-	5.0 ± 1.0	2.0	0.7	40	100	2000	
MO(X)1CM15S	15.0	-	11.5 ± 1.5	2.0	0.8	75	100	2000	
MO(X)2CM20E	20.0	-	4.6 ± 1.0	2.0	0.8	120	100	1000	
MO(X)2CM25C	25.0	-	3.5 ± 1.0	2.0	0.8	120	100	1000	
MOS(X)1/2CM10F	10.0	-	5.0 ± 1.0	2.0	0.6	23	100	2000	
MOS(X)1CM12.5D	12.5	-	4.0 ± 1.0	2.0	0.8	31	100	2000	
MOS(X)1CM15F	15.0	-	5.0 ± 1.0	2.0	0.8	31	100	2000	
MOS(X)2CM15E	15.0	-	4.5 ± 1.0	2.0	0.8	71	100	2000	
MOS(X)2CM20U	20.0	-	13.5 ± 1.5	2.0	0.8	71	100	2000	
MOS(X)3CM20E	20.0	-	4.6 ± 1.0	2.0	0.8	120	100	1000	
SPR(X)1/2CM10F	10.0	-	5.0 ± 1.0	2.0	0.6	23	100	2000	
SPR(X)1CM12.5D	12.5	-	4.0 ± 1.0	2.0	0.8	44	100	2000	
SPR(X)1CM15F	15.0	-	5.0 ± 1.0	2.0	0.8	44	100	2000	
SPR(X)2CM15E	15.0	-	4.5 ± 1.0	2.0	0.8	71	100	2000	
SPR(X)3CM20E	20.0	-	4.6 ± 1.0	2.0	0.8	120	100	1000	

T.C.R. symbol is to be entered in the [ ].