



ZERO OHM JUMPER WIRES JL



MATERIAL

Solder plated copper wire

IDENTIFICATION

PRODUCT CODE	COATING COLOR	MARKING
JL 5	None	-----
JL 6		

All these products have Pb-free terminations and meet EU-RoHS and China-RoHS requirements

TYPE DESIGNATION (HOW TO ORDER)

JL	6	C	T26	A
PRODUCT CODE	NOMINAL DIAMETER 5: 0.5 mm 6: 0.6 mm	TERMINATION SURFACE MATERIAL C: SnCu	TAPING & FORMING T26: 26mm taping T52: 52mm taping	PACKAGING A: Ammo R: Reel

*Please see "PACKAGING"

Contact us when you have control request for environmental hazardous material other than the substance specified by EU-RoHS

DIMENSIONS (mm)

TYPE	W	P	A	ø d (nominal)	T	t	Z
JL 5 C T26	26 +1.0 / 0	5.00 ± 0.30	39 ± 1	0.5	6.2 ± 0.5	2.0 Max.	0.8 Max.
JL 5 C T52	52 ± 1	5.08 ± 0.38	65 ± 1				
JL 6 C T26	26 +1.0 / 0	5.00 ± 0.30	39 ± 1	0.6	6.2 ± 0.5	2.0 Max.	0.8 Max.
JL 6 C T52	52 ± 1	5.08 ± 0.38	65 ± 1				

FEATURES

- Automatic insertion is applicable
- ø 0.5 mm or ø 0.6 mm electro-plated semi-hard copper wire

RATING

PRODUCT CODE	RESISTANCE	MAX. ALLOWABLE CURRENT	NOMINAL DIAMETER
JL 5 C T26	Less than 20mΩ	8 A	0.5 mm
JL 5 C T52			
JL 6 C T26		10 A	0.6 mm
JL 6 C T52			

Contact our sales representatives before you use our products for applications including automobiles, medical equipment and aerospace equipment. Malfunction or failure of the products in such applications may cause loss of human life or serious damage.

Specifications given herein may be changed at any time without prior notice. Please confirm technical specifications before you order or use.